



International Journal of ChemTech Research

CODEN (USA): IJCRGG ISSN: 0974-4290 Vol.9, No.04 pp 625-633, **2016**

Luminescence properties of novel Li₃Ba₂Gd₃ (MoO₄)₈:RE³⁺ (RE= Pr³⁺, Sm³⁺) red phosphors

Anthuvan John Peter*1 And I. B. Shameem Banu²

¹Department of Physics, St. Anne's College of Engineering and Technology, Panruti, Tamilnadu, India

²Department of Physics, B. S. Abdur Rahman University, Vandalur, Chennai, Tamilnadu, India

Abstract: A series of $Li_3Ba_2Gd_{3-x}Pr_x$ (MoO₄)₈ and $Li_3Ba_2Gd_{3-x}Sm_x$ (MoO₄)₈ red phosphors were synthesized by conventional solid state reaction method. For 7 mol % of Pr^{3+} and for 8 mol% of Pr^{3+} and for 8 mol% of Pr^{3+} and for 8 mol% of Pr^{3+} and Pr^{3+} and for 8 mol% and 401 nm (near UV) indicating an intense absorption. The PL emission spectra of Pr^{3+} and Pr^{3+} and at 604 nm (red) which corresponds to Pr^{3+} and Pr^{3+} and at 604 nm (red) which corresponds to Pr^{3+} and Pr^{3+

Keywords: Phosphors, photoluminescence, solid state reaction method, red light.

1. Introduction

Currently, trivalent rare-earth-ion-activated molybdate based phosphors have fascinated great attention for solid-state lighting applications by virtue of their long lifetimes, and efficient luminescence property. The rare-earth ions are represented by a partly filled 4f shell that is completely shielded by $5s^2$ and $5p^6$ orbitals. Therefore, emission transitions provide sharp intense lines in the optical spectra [1, 2]. The use of rare-earth element-based phosphor, based on "line-type" f-f transitions, can narrow the emissions to the visible range, resulting in high efficiency and a high-lumen equivalence. In the recent years, a flourishing care is concentrated on Li₃Ba₂Gd_{3-x}(MoO₄)₈ host matrix for luminescent ions in the interest of their excellent chemical and thermal stability and favourable luminescence characteristics compared to the sulfide- and nitride-based materials. Moreover, these are environmentally friendly as no toxic gases like sulphide are given out. Li₃Ba₂Gd_{3-x}(MoO₄)₈ occur in monoclinic crystal system with space group C2/c in a disordered structure [3]. They are remarkable host matrices for luminescent ions due to their unique structure, good chemical stability, low temperature preparation, superior luminescence features and low cost raw materials. They have also brought a lot of significance for their unique characteristics like ferroelectricity, laser hosts, phosphors and catalysis [4, 5]. The investigations on the luminescence properties of rare earth doped Li₃Ba₂Gd_{3-x}(MoO₄)₈ are scanty. Among these, most of the earlier studies carried on these materials in the past few years specifically focused luminescence properties of the single crystals of Li₃Ba₂Gd₃ (MoO₄)₈ and Li₃Ba₂Gd₃ (MoO₄)₈ activated with various lanthanide ions [6]. Taking into account the above investigations, in the present work. We mainly focus on the synthesis and luminescent characteristics of $Li_3Ba_2Gd_{3-x}Pr_x$ (MoO₄)₈ (x = 0.01, 0.03, 0.05, 0.07 and 0.09 mol) and $\text{Li}_3\text{Ba}_2\text{Gd}_{3-x}\text{Sm}_x$ (MoO₄)₈ (x = 0.02, 0.04, 0.06, 0.08 and 0.10 mol) red phosphor ceramics by a mechanochemically assisted high temperature solid state reaction method. Furthermore, we investigated the

structure, morphology, particle size and photoluminescence (PL) and life time properties of the resulting samples in detail. Finally, from the analysis of the CIE diagram, we propose that the obtained nanoparticles of Pr and Sm doped Li₃Ba₂Gd₃ (MoO₄)₈ phosphors are promising red emitting components which could be used in White LEDs.

2. Experimental Method

2.1 Preparation of Phosphors

The efficient red phosphors of Li₃Ba₂Gd_{3-x}Pr_x (MoO₄)₈ (x= 0.01, 0.03, 0.05, 0.07, 0.09) and Li₃Ba₂Gd_{3-x}Sm_x (MoO₄)₈ (x = 0.02, 0.04, 0.06, 0.08 and 0.10 mol) were synthesized by mechanochemically assisted high temperature solid state reaction method by using AR grade Li₂CO₃, BaCO₃, Gd₂O₃ (99.99% Aldrich), Pr₂O₃ (99.99% Aldrich), Sm₂O₃(99.99% Aldrich) and MoO₃ (99.5% Aldrich) as starting materials without any further purification. The relevant stoichiometric mixtures of starting materials were mixed and were milled for a period of three hours in a high energy planetary ball mill Pulverisette 7 (FRITSCH). Milling was carried out in two grinding vials of 15 ccm volume containing balls with diameter of 12 mm. Both the container and balls were made of tungsten carbide material. The milling speed was fixed at 350 revolutions per minute (rpm). The powder samples were calcined in air at 800 °C for 5h with the heating rate of 5K min⁻¹ to form polycrystalline Li₃Ba₂Gd_{3-x}Pr_x(MoO₄)₈ and Li₃Ba₂Gd_{3-x}Sm_x(MoO₄)₈

2.2 Characterization

X – ray powder diffraction (XRD) analysis was out using Pan Analytical X'pert pro x- ray diffractometer with Cu K-alpha radiation (λ = 1.5406 Å) at a scanning rate of 0.02° per second. The XRD patterns were obtained in the range of $0^{\circ} \le 2\theta \le 70^{\circ}$ and were compared with the JCPDS data. Fourier Transform infrared spectroscopy (FTIR) measurements were carried out in the wavelength range of 400–4000 cm⁻¹ with a Nicolet 6700 FTIR equipped with a deuterated triglycine sulfate detector. The particle size and morphology of the powder samples were inspected by using scanning electronic microscope (SEM Philips XL30). The centrifugal particle size analyzer of Shimadzu SA-CP3 was used to observe the distribution and size of the particles. The measurements of PL and photoluminescence excitation (PLE) spectra were performed by a Jobin Yuvon Flurolog-3-11 Spectroflurometer at room temperature with 450W xenon lamp was used as the excitation source (200-700 nm). The phosphor powders were slackly positioned on a solid stand and were excited straight. The excitation and emission slit width were set to 3 nm. Optical absorption spectra were recorded using Systronics-2101 UV–visible- double beam spectrophotometer. All spectroscopic measurements of the phosphors were carried out at room temperature.

3. Results and discussion

3.1 XRD and size distribution characterization

A typical powder X-ray diffraction (XRD) pattern of selected samples is represented in Fig. 1. It can be observed that all of the peaks match those of scheelite-type Li₃Ba₂Gd₃ (MoO₄)₈ (No.JCPDS 77-0830) structure. The strong and narrow peaks indicate a high crystallinity of the as-prepared products, which is beneficial for high luminescence [3]. The peaks in the XRD spectra are sharp and intense proving that a highly crystalline single-phase of Li₃Ba₂Gd₃ (MoO₄)₈ phosphors with the monoclinic structure of space group C2/c had been successfully prepared without any impurity phase and distortion in crystal structure by mechanochemically assisted high temperature solid state reaction. Therefore, the substitution Pr^{3+} ions and Sm^{3+} were incorporated into the Li₃Ba₂Gd₃ (MoO₄)₈ host lattice without any significant structural change or observed impurity phase. Based on the effective ionic radii of cations reported by Shannon, the ionic radii of Pr^{3+} (r = 1.126 Å, Pr = 1.126 Å, Pr

calculated from (131) peak according to the Debye-Scherrer's equation: $D = \frac{0.0374}{\beta \cos \beta}$

where D is the average grain size, λ represents Cu K α wavelength 0.1542 nm and β is the FWHM of the peak at Bragg angle θ . The estimated results show that the average crystallite size of Li₃Ba₂Gd_{3-x} (MoO₄)₈: x Pr³⁺ (0.01, 0.03, 0.05, 0.07 and 0.09 mol) is about 89 nm and that of Li₃Ba₂Gd_{3-x}Sm_x (MoO₄)₈ (x = 0.02, 0.04, 0.06, 0.08 and 0.10 mol) is about 67 nm respectively.

The particle size distribution, EDAX results and SEM image of $Li_3Ba_2Gd_3$ (MoO₄)₈:0.07 Pr³⁺ and $Li_3Ba_2Gd_3$ (MoO₄)₈:0.08 Sm³⁺ phosphors are shown in Fig. 2 and in Figure.3 respectively. From SEM and particle size distribution data it confirms that the morphologies of $Li_3Ba_2Gd_3$ (MoO₄)₈:0.07 Pr³⁺ and $Li_3Ba_2Gd_3$ (MoO₄)₈:0.08 Sm³⁺ nano particles appear to be highly crystalline and are slightly agglomerated and the particles show a narrow size distribution, with the average diameter of particles at 85 nm for $Li_3Ba_2Gd_3$ (MoO₄)₈:0.07 - Pr³⁺ and 65 nm for $Li_3Ba_2Gd_3$ (MoO₄)₈:0.08 Sm³⁺ indicating that the particles are fit for the fabrication of solid state lighting devices.




Fig.1. Powder XRD patterns of $\text{Li}_3\text{Ba}_2\text{Gd}_{3-x}$ (MoO₄)₈:xPr³⁺ (x= 0.01and 0.09 mol) and $\text{Li}_3\text{Ba}_2\text{Gd}_{3-x}$ (MoO₄)₈:xSm³⁺ (x= 0.02and 0.10 mol)

The average grain size of the near rounded nano particles is about 82 nm and 68 nm which is consistent with the data of the corresponding XRD patterns. The EDAX of $Li_3Ba_2Gd_3$ (MoO₄)₈:0.07 Pr³⁺ and $Li_3Ba_2Gd_3$ (MoO₄)₈:0.08 Sm³⁺ are shown as an example to confirm the presence of the constituent elements. EDAX spectrum shows the respective peaks of the constituent elements such as Lithium (Li), Barium (Ba), Gadolinium (Gd), Oxygen (O), Molybdenum (Mo), Praseodymium (Pr) and samarium (Sm) for EDAX of $Li_3Ba_2Gd_3(MoO_4)_8$:0.07 Pr³⁺ and Gadolinium (Gd) in $Li_3Ba_2Gd_3(MoO_4)_8$:0.08 Sm³⁺ compounds. The stoichiometric proportions of the crystal as well as the EDAX results are in good agreement. The average grain size of the near rounded nano particles is about 82 nm and 68 nm which is consistent with the data of the corresponding XRD patterns.




Fig.2. EDAX (a), Particle size distribution (b), and SEM (c) of Li₃Ba₂Gd₃ (MoO₄)₈:0.07 Pr³⁺ Phosphor




Fig.3. EDAX (a), Particle size distribution (b), and SEM (c) of Li₃Ba₂Gd₃(MoO₄)₈:0.08Sm³⁺ phosphor

3.2 FTIR analysis

The FT-IR spectra of $\text{Li}_3\text{Ba}_2\text{Gd}_3(\text{MoO}_4)_8$:0.07 Pr^{3+} and $\text{Li}_3\text{Ba}_2\text{Gd}_3(\text{MoO}_4)_8$:0.08 Sm^{3+} red nanophosphors prepared by mechanochemically assisted high temperature solid state reaction is shown in Fig. 4




Fig.4. FTIR spectra of Li₃Ba₂Gd_{3-x} (MoO₄)₈: xEu^{3+} (0, 0.01and 0.09 mol) and Li₃Ba₂Gd_{3-x} (MoO₄)₈: xSm^{3+} (x=0.02and 0.10 mol)

The bands at around 3363 cm⁻¹ and at around 1649 cm⁻¹ are assigned to O-H stretching vibration and H-O-H bending vibration, respectively. These two bands are the characteristic vibrations of water molecules absorbed from air by the sample surface. The strong absorption peaks at around 911.9, 807.1 and 728.0cm⁻¹ are assigned to stretching vibration of O-Mo-O in MoO₄²⁻ tetrahedron.

3.3 Photoluminescence Properties of Li₃Ba₂Gd₃ (MoO₄)₈: Pr³⁺:

3.3.1 The excitation and emission spectra of Li₃Ba₂Gd₃ (MoO₄)₈: Pr³⁺ phosphor

Optical properties of Li₃Ba₂Gd₃ (MoO₄)₈: Pr³⁺ (x= 0.01, 0.03, 0.05, 0.07 and 0.09 mol) phosphors prepared by mechanochemically assisted solid state reaction method is shown in Fig. 5 and Fig.6. The excitation spectrum is monitored at the emission wavelength of 645 nm. It can be seen clearly that the excitation spectrum consists of a strong and broadband from 250 to 350 nm with a maximum at about 294 nm and this is the charge-transfer band (CTB) ascribed to the host. In addition to the CTB, some sharp absorption peaks are found in the wavelength region of 450–500 nm, resulting from the excitation of the f–f shell transitions of Pr³⁺ ions, and the excitation bands consist of three main peaks located at 453, 474 and 487 with the maximum excitation wavelength at 453 nm which is in well agreement with the blue wavelength of GaN based LED

chips. These excitation peaks are respectively attributed to the electronic transitions of ${}^{3}H_{4} \rightarrow {}^{3}P_{2}$, ${}^{3}H_{4} \rightarrow {}^{3}P_{1} + {}^{1}I_{6}$, ${}^{3}H_{4} \rightarrow {}^{3}P_{0}$ which are all due to the typical f-f transitions of Pr^{3+} ions (8).




Fig.5. The photoluminescence excitation ($\lambda_{em} = 645$ nm) spectra of Li₃Ba₂Gd_{3-x} (MoO₄)₈: xPr³⁺ (x= 0.01, 0.03, 0.05, 0.07 and 0.09 mol)

Upon excitation at 453 nm, the obtained emission spectrum exhibits four major emission bands at 594, 618,645 and 680 nm, corresponding to the ${}^3P_0 \rightarrow {}^3H_5, {}^3P_0 \rightarrow {}^3H_6, {}^3P_0 \rightarrow {}^3F_2, {}^3P_0 \rightarrow {}^3F_3$ typical transitions of Pr^{3+} respectively. The strongest peak appearing at 645 nm is the characteristic emission of Pr^{3+} with ${}^3P_0 \rightarrow {}^3F_2$ red emission. It was monitored from the PL spectra that the relative intensity of the Pr^{3+} emission increase as the concentration of the Pr dopant increases and reaches a maximum at x=0.07. With further of addition of Pr^{3+} PL decreases because of the concentration quenching which is caused by the energy transfer between the identical Pr^{3+} ions. This promotes an increase of the non-radiative relaxation and may be responsible for the Pr^{3+} luminescence inhibition in Gd system beyond 7 mol% [9].

3.3.2 The excitation and emission spectra of Li₃Ba₂Gd₃ (MoO₄)₈:

 Sm^{3+} phosphor Optical properties of the $Li_3Ba_2Gd_{3-x}Sm_x$ (MoO₄)₈ (x = 0.02, 0.04, 0.06, 0.08 and 0.10 mol) phosphors prepared by mechanochemically assisted solid state reaction method is shown in Fig. 7 and Fig. 8.




Fig.6. The photoluminescence emission ($\lambda ex = 450$ nm) spectra of Li₃Ba₂Gd_{3-x} (MoO₄)₈:xPr³⁺ (x= 0.01, 0.03, 0.05, 0.07 and 0.09 mol)

The excitation spectrum (λ_{em} = 605 nm) transitions consist of a most intense and broad excitation band in the range from 225 nm to 330 nm (CTS) and very sharp peaks with remarkable intensity in the range from 330 nm to 500 nm which corresponds to the typical Sm³⁺ intra – 4f transitions in the host lattice. The strong absorption at 404 nm is attributed to the ${}^6H_{5/2}$ ${}^4G_{7/2}$ transition of Sm³⁺ which is in good agreement with the near-UV wavelength of GaN based LED chips (12).




Fig.7. The photoluminescence excitation ($\lambda_{em} = 605$ nm) spectra of Li₃Ba₂Gd_{3-x} (MoO₄)₈:x Sm³⁺ (x= 0.02, 0.04, 0.06, 0.08 and 0.10 mol)

Upon excitation at 404 nm (near UV), the obtained emission spectra exhibits three sharp lines which are associated with the ${}^4G_{5/2} \rightarrow {}^6H_J$ (J = 5/2, 7/2,9/2) transitions from the excited Sm³⁺ to the ground state as shown in Fig.8. The main emission peak is the ${}^4G_{5/2} \rightarrow {}^6H_{7/2}$ transitions of Sm³⁺ at 605 nm (red). Other transitions located in the range of 530 nm to 750 nm are weak. The optimum concentration of Li₃Ba₂Gd_{3-x}Sm_x (MoO₄)₈ (x = 0.02, 0.04, 0.06, 0.08 and 0.10 mol) at which maximum emission occurs is found to be 8 mol%.




Fig. 8. The photoluminescence emission ($\lambda_{ex} = 404$ nm) spectra of Li₃Ba₂Gd_{3-x} (MoO₄)₈:xSm³⁺ (x= 0.02, 0.04, 0.06, 0.08 and 0.10 mol)

3.3.3 CIE analysis:

In general, color is expressed by means of color coordinates disclosed by the Commission International de l'Eclairage (CIE) 1931, a two-dimensional graphical representation of any color perceptible by the human eye on an x–y plot. Fig.9 shows the CIE chromaticity diagram for Li₃Ba₂Gd₃ (MoO₄)₈: 0.07 Pr³⁺, Li₃Ba₂Gd₃ (MoO₄)₈: 0.08 Sm³⁺, CaMoO₄: Eu³⁺ and Y₂O₂S: Eu³⁺ phosphors. The CIE chromaticity coordinates (x, y) of the Li₃Ba₂Gd₃ (MoO₄)₈: 0.07 Pr³⁺, Li₃Ba₂Gd₃ (MoO₄)₈: 0.08 Sm³⁺, CaMoO₄: Eu³⁺, Y₂O₂S: Eu³⁺ phosphors are (0.689, 0.305), (0.601, 0.396), (0.678, 0.322) [10] and (0.662, 0.334) [11] respectively. Hence, the CIE diagram illustrates that the obtained phosphor nanoparticles of Pr and Sm doped Li₃Ba₂Gd₃ (MoO₄)₈ show intense red emissions when excited by a single wavelength (λ_{ex} =450 nm and λ_{ex} =404 nm) and thus the obtained results confirm that mechanochemically assisted sintered Li₃Ba₂Gd₃ (MoO₄)₈: 0.07 Pr³⁺ and Li₃Ba₂Gd₃ (MoO₄)₈: 0.08 Sm³⁺ phosphors are promising red emitting components which could be used in White LEDs. Fig.10 presents the photoluminescence decay curves and lifetime of Pr³⁺ (3 P₀ \rightarrow 3 F₂, 645 nm) and sm³⁺ (4 G_{5/2} \rightarrow 6 H_{7/2}, 605 nm) in the as-prepared Li₃Ba₂Gd₃ (MoO₄)₈:0.07 Pr³⁺, Li₃Ba₂Gd₃ (MoO₄)₈: 0.08 Sm³⁺ phosphors. This can be fitted by a single-exponential function as I=Aexp (-t/ τ) (τ is the life time of rare earth ion), and the value of lifetime of Pr³⁺ is 0.321 ms and of Sm³⁺ is 0.310 ms. The result shows that the lifetime is short enough for potential applications in displays and lights.




Fig. 9. CIE chromaticity diagram for Li₃Ba₂Gd₃ (MoO₄)₈:0.07Pr³⁺, Li₃Ba₂Gd₃ (MoO₄)₈:0.08 Sm³⁺, CaMoO₄: Eu³⁺, Y₂O₂S: Eu³⁺ phosphors.




Fig. 10. Room temperature luminescent decay curves of $^3P_0 \rightarrow ^3F_2$ transitions at 645 nm of Pr^{3+} ions of $Li_3Ba_2Gd_3$ (MoO₄)₈:0.07 Pr^{3+} phosphor and $^4G_{5/2} \rightarrow ^6H_{7/2}$ transitions at 605 nm of Sm^{3+} ions of $Li_3Ba_2Gd_3$ (MoO₄)₈:0.08 Sm^{3+} phosphor

As the present work is focused for the purpose of red phosphor application in WLED with near UV/blue GaN based chips as excitation sources, the results of the excitation and emission spectra of the present work are compared with that of emission spectra of the conventional red phosphor Y₂O₂S: Eu³⁺ prepared by solid state reaction method. For this purpose, the commercial red phosphor Y₂O₂S: Eu³⁺ was prepared by solid state reaction (SSR) method and the luminescence properties were also studied. The red emission spectra of these red phosphors are presented in Fig.11 which reveals that red emission intensity of Li₃Ba₂Gd₃ (MoO₄)₈:0.07 Pr³⁺ and Li₃Ba₂Gd₃ (MoO₄)₈:0.08 Sm³⁺ are comparable with that of commercial Y₂O₂S: Eu³⁺ red phosphor, indicating that Li₃Ba₂Gd₃ (MoO₄)₈:0.07 Pr³⁺ and Li₃Ba₂Gd₃ (MoO₄)₈:0.08 Sm³⁺ phosphors prepared by mechanochemically assisted high temperature solid state reaction is a promising red phosphor for WLEDs.




Fig. 11. Comparison of emission spectra of Li₃Ba₂Gd₃ (MoO₄)₈:0.07 Pr³⁺, Li₃Ba₂Gd₃ (MoO₄)₈:0.08Sm³⁺ and Y₂O₂S: Eu³⁺ phosphors.

4. Conclusion:

Highly luminescent red nanophosphors of $Li_3Ba_2Gd_3$ (MoO₄)₈:RE³⁺ (RE= Pr³⁺, Sm³⁺), with pure single phase and with different gain sizes, were successfully prepared by mechanochemically assisted high temperature solid state reaction method. Upon 450 nm blue excitation, the $Li_3Ba_2Gd_3$ (MoO₄)₈:0.07 Pr³⁺ phosphor showed strong red emission lines at 645 nm. The optimum doping concentration of Pr³⁺ content in $Li_3Ba_2Gd_3$ (MoO₄)₈ for the enhanced red emission is found to be 7mol%. Upon 404 nm near UV excitation, the $Li_3Ba_2Gd_3$ (MoO₄)₈:0.08Sm³⁺ phosphor showed intense red emission lines at 605 nm. The optimum doping concentration of Sm³⁺ content in $Li_3Ba_2Gd_3$ (MoO₄)₈ for the enhanced red emission are found to be 8mol%. The red emission intensity of $Li_3Ba_2Gd_3$ (MoO₄)₈:0.07 Pr³⁺ and $Li_3Ba_2Gd_3$ (MoO₄)₈:0.08Sm³⁺ are much comparable with that of conventional Y_2O_2S : Eu³⁺ red phosphor. This suggests that $Li_3Ba_2Gd_3$ (MoO₄)₈:0.07 Pr³⁺ and $Li_3Ba_2Gd_3$ (MoO₄)₈:0.08Sm³⁺ nanophosphors are suitable red-emitting phosphors in near UV / blue light GaN based White LEDs.

References

- 1. PVSSSN Reddy, Ch.Satya Kamal, K.Sujatha, T.Samuel, M.Indiradevi, Y.Rama Krishna and K.Ramachandra Rao, Enhanced photoluminescence of Tb3+ co-doped La2O3:Bi3+nanophosphors material using ethylene glycol route, International Journal of ChemTech Research, Vol.8, No.12,2015, pp (741-751).
- 2. Anthuvan John peter and I. B. Shameem Banu, Luminescent properties of Tb3+ doped CaMoO4 nanophosphor for fluorescent lamp application, International Journal of ChemTech Research, Vol.8, No.3, 2015, pp (1083-1087).
- 3. M. Venkateswarlu and B.H. Rudramadevi, Spectral analysis of europium doped Borate Zinc Magnesium glass, International Journal of ChemTech Research, Vol.7, No.2, 2015, pp (607-612).
- 4. Ayman H. Ahmed, Recent Advances in the Syntheses and Characterization of Polymer-anchored Transition Metal Complexes, International Journal of ChemTech Research, Vol.6, No.1,2014,PP (36-52).

- 5. Bijini B.R , Prasanna S , Deepa M, Mohanakumaran Nair C and Rajendrababu K, Spectral, Thermal, Dielectric Studies and Crystal Structure of Novel Nonlinear Optical Diaquabis(Salicylato)Zinc, International Journal of ChemTech Research, Vol.4, No.2, 2012, pp (739-748).
- 6. Liang H, Tao Y, Su Q, Wang S, "VUV–UV Photoluminescence Spectra of Strontium Orthophosphate Doped with Rare Earth Ions", J. Solid State Chem., Vol.167, 2002, pp(435 440).
- 7. Li P. L, Wang Z. J, Yang Z. P, Guo Q. L, and Li X, "Emission features of LiBaBO₃:Sm³⁺ red phosphor for white LED", Mater. Lett, Vol. 63, 2009, pp. (751-753).
- 8. Quhong Z, Jing W, Mei Z, Weijia D, and Qiang S, "Luminescence Properties of Sm^{3+} doped $Bi_2ZnB_2O_7$ ", J. Rare Earths, Vol.24, 2006, pp. (392-395).
- 9. Hu L. Y, Song H. W, Pan G. H., Yan B, Qin R. F, Dai Q. L, Fan L. B, Li S. W, Bai X, "Photoluminescence properties of samarium-doped TiO₂semiconductor nano crystalline powders", J. Lumin., Vol. 127, 2007, pp(371-376).
- 10. Weng M. H, Yang R. Y, Peng Y. M, Chen J. L, "Yellowish green-emitting KSrPO₄:Tb³⁺ phosphors with various doping concentrations prepared by using microwave assisted sintering", Ceram. Int., Vol. 38, 2012,pp. (1319-1323).
- 11. John Peter A., Shameem Banu I. B., Samuel Paul D, Thirumalai J, "Enhanced luminescence in CaMoO₄: Eu³⁺ red phosphor nanoparticles prepared by mechanochemically assisted solid state meta-thesis reaction method", J. Mater. Sci. Mater. Electron., Vol. 24, 2013 pp(4503–4509).
- 12. Zhou L.Y, Wei J.S, Yi L.H, Gong F.Z, Huang J.L, and Wang W, "A promising red phosphor MgMoO₄:Eu³⁺ for white light emitting diodes", Mater. Res. Bull., Vol.44, 2009,pp(1411-1414).

